

ANCHORAGE CONNECTORS

Drop In/Drop Thru Anchors



Removable Anchors

Removable Anchors, developed for fall protection, are safe, lightweight, and surprisingly simple to employ. PeakWorks manufactures 2 styles of removable anchors

- 1) Drop Thru Anchors
- 2) Concrete anchors

Drop Thru Anchors

The Drop Thru Anchor is a removable and reusable anchor designed for overhead applications. Available in three different sizes 4", 6", 12" diameter plates. Simply insert the cable end of the anchorage connector to an approved anchor and begin using it. Once the task is complete simply pull the cable back through the opening and its ready to be re-used.

Concrete Anchors

PeakWorks anchors have been tested to meet **ANSI Z359.7**. They have a long list of benefits above competitive products. A few include:

- Ease of use – simply drill the proper size hole into your concrete, blow the dust out with compressed air, and insert the unit.
- Multi-directional attributes – PeakWorks Removable anchors work in horizontal, vertical and overhead surfaces.
- Reusability – when your job is done, simply fill in the drilled hole if necessary and reuse at your new desired location.



V8223140
AC-9452-DTA-4



V8223145
AC-9452-DTA-12



V8222120
CP-12010-1



V8221121
CP-12010-2

PROD. NO.	MOD. NO.	Product Name	Size of Open/ hole to install thru/ in	Application
V8223140	AC-9452-DTA-4	DRP THRU ANCHOR 4" PLATE, 8 FT CABLE	1-3/4" to 2"Ø min hole size (4.1cm to 4.4cm)	Temporary
V8223142	AC-9452-DTA-6	DRP THRU ANCHOR 6" PLATE, 8 FT CABLE	1-3/4" to 2"Ø min hole size (4.1cm to 4.4cm)	Temporary
V8223145	AC-9452-DTA-12	DRP THRU ANCHOR 12" PLATE, 8 FT CABLE	1-3/4" to 2"Ø min hole size (4.1cm to 4.4cm)	Temporary
V8222120	CP-12010-1	3/4" (19 mm) Concrete Hole Anchor	3/4" (19 mm)	Temporary
V8221121	CP-12010-2	3/4" (19 mm) Toggle-Lok Anchor	3/4" (19 mm)	Temporary