



Specification & Data Sheet

Dual Self-Retracting Lifelines LE (SRL-LE)-CLASS A

ORDERING INFORMATION

Product No.	Model No.	Webbing/Cable ft (m)	Length ft (m)	Weight
V845525006LE	SRL-50502-6LE	1" (25 mm) Webbing	6 ft (1.8 m)	5.5 lbs (2.5 kg)
V845526006LE	SRL-50602-6LE	1" (25 mm) Webbing	6 ft (1.8 m)	7.4 lbs (3.3 kg)



V845526006LE
SRL-50602-6LE



V845525006LE
SRL-50502-6LE

TECHNICAL SPECIFICATIONS

- Capacity:** 136 kg (300 lbs) combined weight of person, tools, clothing, etc. One person use only.
- Storage:** Store in a cool dry place away from chemicals, water, corrosive environments, and sources of heat or spark
- Operating Temperatures:** -35°C to +35°C
- Leading Edge:** Approved for use in vertical and horizontal applications.
- Max Total Arrest Distance:** 24 in. (0.61 m)
- Average Arrest Force:** 765 lbf (3.4 kn)

STANDARD COMPLIANCE

Certified to meet OSHA, ANSI Z359.14-2014, Class A, Leading Edge and CSA Z259.2.2 standards

MATERIALS

- Housing:** Aluminum
- Lifeline:** 1" (25 mm) Dyneema Webbing
- Snaphook:** Steel
- Carabiner:** Steel
- Form Hook:** Aluminum

Description and Performance:

Peakworks offers a new series of self-retracting lanyards that meet or exceed the newest most stringent standards for leading edge applications (LE). Leading edge SRL's are designed to protect a worker when working near an edge and a fall hazard exists. They provide additional protection against sharp or abrasive surfaces found on many construction sites. The lightweight, durable, aluminum housing unit is approved for use in vertical and horizontal applications. The attachment points include a swivel eye on housing with connection pin for mounting below the dorsal D-Ring and double action locking form hooks with fall indicator on web lifeline for connection to anchorage connector.

Warnings: See Operating and Maintenance Instruction Manual for details.

Sellstrom Manufacturing Co.
Elgin, IL 60123
Phone: (800) 323-7402
Fax: (847) 358-8564
www.sellstrom.com

